

Artwork Guide


Please read through the checklist for providing design files. Remember: If your files do not meet our specifications, your product may be printed incorrectly. If you do not supply artwork which matches our requirements, we will ask you to resupply it or charge you for the time it takes to adjust.

1. File Format

ai, eps or pdf are the preferred file format. These are created in illustrator. psd, jpg or tiff (300 dpi)

2. Artwork Setup

- Sticker Set Up



Trim : 30x30mm
Bleed : 34x34mm (2mm on each side of trim line)
Safe Area : 26x26mm (internal bleed)



Trim : 60x40mm
Bleed : 64x44mm (2mm on each side of trim line)
Safe Area : 56x36mm (internal bleed)



Trim

This line is where we aim to cut (actual cutting line).



Bleed

2mm bleed is required for the printing process.

Please make sure background needs to extend into the bleed area, the bleed ensures unprinted white edges after trimming.




Safe Area


Please make sure all important information and graphics are contained in this box otherwise you risk losing it.

- Business Card Set up

STANDARD



Trim : 90x50mm
 Bleed : 94x54mm (2mm on each side of trim line)
 Safe Area : 86x46mm (internal bleed)



Trim : 90x50mm
 Bleed : 96x56mm (3mm on each side of trim line)
 Safe Area : 86x46mm (internal bleed)

DIE-CUT

Trim

This line is where we aim to cut (actual cutting line).

Bleed

2mm bleed is required for the printing process.

Please make sure background needs to extend into the bleed area, the bleed ensures unprinted white edges after trimming.

Safe Area

Please make sure all important information and graphics are contained in this box otherwise you risk losing it.

2. Colour

All colour mode must be converted to CMYK We will not take any responsibility for print results like discolouration or unexpected outcome when you supplied file as RGB or PANTONE.

C 70 M 50 Y 0 K 0	C 80 M 50 Y 0 K 0	C 90 M 50 Y 0 K 0
C 70 M 60 Y 10 K 10	✓ C 80 M 60 Y 10 K 10	C 90 M 60 Y 10 K 10
C 70 M 70 Y 20 K 10	C 80 M 70 Y 20 K 10	C 90 M 70 Y 20 K 10
C 10 M 80 Y 80 K 10	C 20 M 80 Y 80 K 10	C 30 M 80 Y 80 K 10
C 10 M 90 Y 90 K 10	✓ C 20 M 90 Y 90 K 10	C 30 M 90 Y 90 K 10
C 10 M 100 Y 100 K 10	C 20 M 100 Y 100 K 10	C 30 M 100 Y 100 K 10
C 60 M 40 Y 70 K 10	C 70 M 40 Y 70 K 10	C 80 M 40 Y 70 K 10
C 60 M 50 Y 80 K 10	✓ C 70 M 50 Y 80 K 10	C 80 M 50 Y 80 K 10
C 60 M 60 Y 90 K 10	C 70 M 60 Y 90 K 10	C 80 M 60 Y 90 K 10

- All colour mode must be converted to CMYK

- We will not take any responsibility for print results like discolouration or unexpected outcome when you supplied file as RGB or PANTONE.
VIEW [COLOUR GUIDE](#)
- Useful Information Full Colour Colour Variation Chart


3. Font

All fonts must be outlined or embedded. Fonts must be no less than 6pt. Since there are literally thousands of fonts available on both Mac's and PC's, it can become tricky to be sure that everyone has access to the same fonts and are able to see your images properly (illustrator and photoshop documents). When a design file is supplied with missing fonts, a printer cannot proceed with your file for production. To solve this issue, please convert text to outlines or send actual font files. Select "Create Outlines" on your computer to do this.



4. Image Resolution

Images created in Photoshop require a minimum 300 dpi resolution. Stroke Weight has to be a minimum of 0.25pt.



300dpi



150dpi



72dpi



5. Stroke

Weight has to be a minimum of 0.25pt